

Series 100 · sliding · lift & slide

HTA-100 SL

Thermally broken sliding and lift & slide window

ZHONG-YAN catalogue: 100系列 隔热断桥推拉窗/提升推拉窗 – 100 series, thermally broken sliding / lift & slide window, sheet 21



Assembled product detail

A thermally broken window in two versions: sliding and lift & slide. Frame thermal break 29 mm, sash 22 mm; frame wall 1.8 mm, sash 1.5–1.8 mm; all-EPDM sealing. Infill up to 30 mm, manual blinds inside the glazing unit available; Siegenia hook locks.

Engineering

Alloy	6063-T5
Wall thickness	frame 1.8 · sash 1.5–1.8 mm
Thermal break	frame 29 · sash 22 mm
Glazing	5mm+20A+5 manual blinds inside the glazing unit available (5+20A with blinds+5)
Max. infill thickness	30 mm
Hardware	Siegenia hook locks with recessed handles
Seals	all EPDM

Field of application

The manufacturer names no climate for this series.

Six matt finishes

The colours of the range per sheets 25–26 of the manufacturer’s catalogue. JL codes are the manufacturer’s codes.



Matte white
JL565S



Matte grey
JL568S




Matte coffee
JL566S



Matte green
JL180S



Matte camel
JL228S



Matte black
JL729S

Colour in print and on screen is a guide, not colorimetry. RAL correspondence is not stated in the manufacturer’s catalogue.

Contacts

Hi-Tech Aluminium Products – representative of ZHONG-YAN systems in Kazakhstan.

Phone **+7 706 646 68 46**

WhatsApp **+7 706 646 68 46**

Website **htalum.kz**

Legal entity **Hi-Tech Aluminium Products LLP**

For a quote, send the city, number of storeys and the opening schedule – we will select a series and prepare a specification.

About this catalogue

Compiled by HTA from the ZHONG-YAN manufacturer’s catalogue «[中亚系统产品手册](#)»: every system gives its sheet. GB classes are declared by the manufacturer. The manufacturer’s catalogue gives no prices or lead times – we calculate both for each project from the opening schedule.